# ramplo

# A WORLD-KNOWN PRODUCER OF HIGH QUALITY WAREHOUSE EQUIPMENT

We offer a unique combination of low prices and excellent quality

All rights and changes reserved. All trademarks mentioned are the property of their respective owners. No part of this publication may be reproduced and/or published by means of printing, photocopying, microfilm, or any other means whatsoever without prior written permission of FEROPORTO Sp. z o.o.



# **ABOUT US**

## OUR COMPANY IS ONE OF THE FAMOUS MANUFACTURERS OF MOBILE LOADING EQUIPMENT IN EU







# **OUR ACHIEVEMENTS**





**17 years of experience** in the production of loading equipment



the range of our equipment includes even more **than 20 types of warehouse equipment** and forklift attachments



supplied equipment to more than **35 countries** worldwide



we **provide a solution** to any challenge of your customer and that's what makes us unique

more than **1000 satisfied** clients over the world and this is just the beginning!



471 special designed products sold



own modern factory



produced **over 1120** items

OUR MAIN GOAL to make our client happy with the successful completion of his project!

## **OUR PRODUCTS**



LOADING RAMPS















## FORKLIFT ATTACHMENTS





# LOADING RAMPS



# LOADING RAMPS



The loading ramps are manufacturing according to the latest innovative technology, with high-strength metal and comply with European and international CE quality standards





The safe design, in the form of a inclined platform that balances the difference between the ground / warehouse surface and the truck body, can be used on any loading area

PROFITABLE INVESTMENT AND HUGE TIME AND MONEY SAVINGS WITHOUT MUCH EFFORT

## MOBILE LOADING RAMPS STANDARD MODEL RL-MR

The mobile ramp is a height-adjustable equipment which allows the forklift to load and unload trucks, railway cars, containers, etc., acting as a mobile bridge.

This is the most popular type of mobile ramp on sale, the ramp is equipped with a manual hydraulic system for height adjustment and solid rubber wheels that allow the ramp to move on any ground surface.



#### Features of the RAMPLO mobile ramps RL-MR:

- load capacity from 6 to 12 tons and more;
- total length (L) from 9010 to 13010 mm and more;
- total width (D) from 2230 to 2350 mm and more;
- height level (N) from 890 mm to 1740 mm;
- wheel sets;
- hydraulic / electric pump.



# **ADDITIONAL OPTIONS\***

# <u>ramplo</u>

# FOR MOBILE RAMPS



**2SL** Safety legs



**EHP** Electrohydraulic station



**ZSRS** Zinc-coated anti-skid grating



**HR** Additional handrails



**EHMP** Electrohydraulic station and manual pump



**TC** Tent cover



**2SL3SW** 3-sides unloading



**SRS** Anti-skid grating





**4WL** Additional pair of wheels



**ZRS** Zinc-coated grating

\* additional options depend on the selected ramp model

## MOBILE LOADING RAMPS ECONOMY MODEL RL-MREC

As well as other types of mobile ramps, this one due to its small dimensions allows operate the ramp comfortable and easily, simplify and speed up logistics operations in warehouses for unloading and loading packaged goods for budget projects.

The ramp is equipped with telescopic legs for the height adjustment and with rollers for movement.



# <u>ramplo</u>



#### Features of the RAMPLO mobile ramps RL-MREC:

- loading capacity from 5 to 9 tons and more;
- total length (A+B+C+D) from 8000 mm and more;
- carriageway width of the horizontal part (F1) from 2010 mm and more;
- operating height (H-J) 940-1340 mm.

# MOBILE LOADING RAMPS

The luxe model of the mobile loading ramp is equipped with a powerful hydraulic system with two cylinders and an eco-friendly metal oil tank. The roadway of the ramp is covered with a hot-dip galvanized anti-skid grating, which makes it safe to drive on the ramp in all weather conditions. For moving the ramp, it is equipped with reliable wheels like in a forklift.

# 

#### Features of the RAMPLO mobile ramps RL-MRLX:

- load capacity from 8 to 16 tons and more;
- total length (L) from 9420 to 13420 mm and more;
- carriageway width (D) from 2010 to 2510 mm and more;
- operating height (N-X) 890-1740 mm.

## **ADDITIONAL OPTIONS RL-MRLX:**

SL – Safety supporting legs
HR – Protective removable handrails
EHP – Electric (220V) hydraulic power station with a control panel
EHBP – Electric (12V) hydraulic station with a battery pack
TC – Tent cover

**CLR** – Another color









# **CUSTOM LOADING RAMPS**

### FEATURES OF THE RAMPLO EQUIPMENT, WHICH CAN BE CHANGED UPON CUSTOMER'S REQUEST:



Our products are not only standard models of equipment, we also produce individual orders / requests according to all customer requirements.

Based on our huge experience in production, our engineers and designers create loading equipment of any design and load capacity.



## **ADDITIONAL OPTIONS\*** FOR CUSTOM LOADING RAMPS



**2SL** Safety legs



**HR** Additional handrails



**HA** Height adjustment



**2SL3SW** 3-sides unloading



**4WL** Additional pair of wheels



**EHP** Electrohydraulic station



**EHMP** Electrohydraulic station and manual pump



**SRS** Anti-skid grating



**ZRS** Zinc-coated grating



**DL** Inside dock leveller



**ZSRS** Zinc-coated anti-skid grating



**AB** Additional connection bridge



**TC** Tent cover



**BR2** Hydraulic folding bridge



\* additional options depend on the selected ramp model

# FIXED LOADING RAMPS

- The construction of fixed loading ramps are made entirely of metal.
- Instead of expanded metal sheets on the ramp's roadway we used steel grating, which allows to avoid holding rainfall / debris on the surface and save longevity of the ramp.
- Thanks to the frame, made of profile pipes, the ramp is light, and the load on the base is less, the ramp is easy to install.
- Fencing, along both sides of the ramp, serves as a bumper and prevent forklift driving beyond the ramp's side edges.
- Load is distributed between several support points.
- The strong 12 mm thick connection bridge.



## Features of the RAMPLO fixed ramps with horizontal platform RL-FXH:

- load capacity from 6 to 10 tons and more;
- total length (L) from 10770 to 12770 mm and more;
- total width (O) from 2230 mm and more;
- horizontal board for the safe forklift movement.

## Features of the **RAMPLO** fixed ramps without horizontal platform **RL-FX**:

- load capacity from 6 to 10 tons and more;
- total length (L) from 8270 to 12270 mm and more;
- total width (O) from 2230 mm and more.









ramplo

# FIXED LOADING RAMPS

# <u>ramplo</u>

This is special designed truck ramp for loading and unloading commercial vehicles at standard dock gates of modern warehouse. Our equipment helps to eliminate difference in heights of commercial vehicles (550-650 mm) and height of dock gates, dedicated for big semitrailers (1100-1200 mm). The construction is designed to for driving forklifts, vans, cars and other transport inside and outside warehouse. Connects 0 ground level and height of warehouse (usually about 1200 mm).



#### Features of the RAMPLO levelling ramps for LCV RL-LCVR:

- load capacity from 5 to 8 tons and more;
- total length (IH) from 11000 to 13000 mm and more;
- total width (O) from 2450 to 6100 mm and more;
- height level (N) from 550 to 650 mm and more.





### Features of the RAMPLO dock access ramps RL-GD:

- load capacity from 6 to 10 tons and more;
- total length (IC) from 6270 to 12270 mm and more;
- total width (O) 2120 mm and more;
- height level (N) from 1100 to 1200 mm and more.



## **ADDITIONAL OPTIONS\***

## FOR FIXED LOADING RAMPS

FX FXH GD LCVR



**FX FXH GD LCVR** 



**HR** Additional handrails

FX FXH GD LCVR



**SRS** Anti-skid grating

FX FXH GD LCVR



FX FXH GD LCVR



**LDP** Ladder with platform

FX FXH GD LCVR



**ZRS** Zinc-coated grating

FX FXH GD LCVR





**LD** Ladder to the ramp

### FX FXH GD LCVR



**ZSRS** Zinc-coated anti-skid grating FX FXH GD LCVR

\* additional options depend on the selected ramp model

# LOADING PLATFORMS



The loading platforms easily enlarges the storage area, allows convenient approach of the truck, gives more space for maneuvering of warehouse equipment, and enlarges the area for other actions with the goods before or after loading / unloading to / from the truck.







#### Features of the RAMPLO loading platforms RL-LMP:

- load capacity from 3 to 12 tons and more;
- total length (IC) from 4270 to 6270 mm and more;
- total width (O) from 2400 to 2800 mm and more;
- height level (N) from 1100 to 1200 mm and more.



# **ADDITIONAL OPTIONS**

### FOR LOADING PLATFORMS



**HA1** Height adjustment on 1 side



**LD** Ladder for pedestrians



**RF** Roof above platform



**RRB** Rubber bumpers rectangular



**HA2** Height adjustment on 2 sides



LDP Ladder with the platform



**TC** Tent cover



**DRBO** Rubber bumpers on O side



**WL** Pair of wheels



**DL** Inside dock leveller



**ZSRS** Zinc-coated anti-skid grating



**DRBI** Rubber bumpers on I side



**HRO** Hand rails on 1 side O



AB Additional connection bridge



**SRS** Anti-skid grating



**WGD** Wheel guides for truck



**HRI** Hand rails on 1 side l



**BR2** Hydraulic folding bridge



**ZRS** Zinc-coated grating



**CLR** Choosing a different color

# OTHER WAREHOUSE EQUIPMENT WE PRODUCE







## WHY CHOOSE US





### WHAT ALL THESE COMPANIES GOT AFTER RECEIVING OUR EQUIPMENT?





they made unloading and loading of any product 2-3 times faster they have saved on labor costs and optimized logistics processes



with mobile ramp their companies also became mobile!



they have invested in equipment that will work for their business for years to come



in addition, the equipment is versatile because it is heightadjustable, i.e. suitable for all types of transport

# ramplo



We always offer the perfect combination of low prices and high quality



All rights and changes reserved. All trademarks mentioned are the property of their respective owners. No part of this publication may be reproduced and/or published by means of printing, photocopying, microfilm, or any other means whatsoever without prior written permission of FEROPORTO Sp. z o.o.

